

ISOPROPYLMAGNESIUM CHLORIDE IN THF (iPrMgCl)

CAS No. 1068-55-9

QS-PDS-053 Revision: 00

FMC Product Code No. 653-01

| | |
|----------------------|--|
| Product Names | Isopropylmagnesium chloride, iPrMgCl |
| Formula | C ₃ H ₇ MgCl |
| Appearance | Brown/gray liquid |
| Application | Isopropylmagnesium chloride, namely a Grignard reagent, is used primarily to add an <i>iso</i> -propyl group to carbonyl groups. This reagent can also be used as a strong base in aprotic solvents. For reviews see: 1) <i>J. Am. Chem. Soc.</i> 1967 , 89, 1964; 2) <i>Synthesis</i> 1977 , 18; and 3) <i>Pure Appl. Chem.</i> 1980 . |

| | |
|------------------------------|------------------------------------|
| Product Specification | <u>Guaranteed*</u> |
| Isopropylmagnesium chloride | 19.0 – 21.0 wt.% (1.8 – 2.0 Molar) |

* This product can be made to agreed upon customer specifications, including various concentrations and carrier systems.

Solvent Tetrahydrofuran (THF)

| | | |
|----------------------------|-------------------------------|----------------|
| Physical Properties | Molecular weight | 102.84 |
| | Density @20°C | 0.975 g/mL |
| | Boiling point of pure solvent | 66°C (THF) |
| | Volatiles, % by weight | 79 - 81% |
| | Pyrophoricity | Non-pyrophoric |
| | Flash Point | -18°C |

Solubility Crystallizes at <5°C.

Thermal Stability Stable under recommended storage conditions.

Air Treatment Construction Energy Fine Chemicals Glass & Ceramics Greases & Lubricants Polymers Pool Water Treatment

**NORTH AMERICA
AND HEADQUARTERS**
FMC Lithium
Seven LakePointe Plaza
2801 Yorkmont Road, Suite 300
Charlotte, NC 28208
P: +1.704.426.5300
F: +1.704.426.5370

EUROPE
FMC Chemicals
Commercial Road
Bromborough
Merseyside
CH62 3NL, England
P: +44.151.482.7356
F: +44.151.482.7361

JAPAN
FMC Lithium
9F, Aoyama Building
1-2-3, Kita-Aoyama
Minato-ku, Tokyo
107-0061, Japan
T: +81.3.3402.3716
F: +81.3.3402.3700

CHINA
FMC Lithium
15F Far East International Plaza
No. 317 Xianxia Road
Shanghai 200051 P. R. China
T: +86.21.6235.1919
F: +86.21.6235.1917

INDIA
FMC India Private Limited
Embassy Star
8, Palace Road
High Grounds
Bangalore 560052, India
T: +91.80.2238.4311
F: +91.80.2238.5255

TAIWAN
FMC Lithium
9F-1, 263 Tun Hwa S. Rd.
Sec. 1
Taipei, Taiwan
T: +866.2.2705.4400
F: +866.2.2702.7460

MARKETS SERVED

ISOPROPYLMAGNESIUM CHLORIDE IN THF (iPrMgCl)

CAS No. 1068-55-9

FMC Product Code No. 653-01

Toxicity/Safety Data

Flammable liquid. Water reactive. In case of fire, do not use water or carbon dioxide.

Corrosive to the eyes (may cause blindness), skin, mucous membranes and upper respiratory tract. Inhalation of vapors may cause dizziness, nausea, anesthesia, numbness, motor weakness in fingers and toes, incoordination, and headache.

ADDITIONAL INFORMATION ON SAFETY IS CONTAINED IN THE FMC NEW PRODUCT DATA SHEET (NPDS) AVAILABLE FOR THIS PRODUCT.

Handling/Storage/Disposal

Use in a closed system under argon or nitrogen. Do not get in eyes, on skin or clothing. Do not breathe vapors or mist.

Store in a cool place. Storage temperature should be 5°C to 40°C. Keep container closed. Keep away from sources of ignition, water, air, acids and oxidizing agents.

Shipping Containers

| | |
|-----------------|-------------------------|
| Bulk containers | 2500 – 20000 L |
| Cylinders | #5 – 420 L |
| Drums | 55 Gal |
| Glass bottles | 125 mL, 500 mL, and 1 L |

Shipping Limitations

Shipments of Isopropylmagnesium chloride in THF are described as "Organometallic substance, liquid, water-reactive, flammable (*ISOPROPYLMAGNESIUM CHLORIDE, TETRAHYDROFURAN, SOLUTION*) 4.3 (3), UN 3399, PG I." Shipments require "Dangerous When Wet" and "Flammable Liquid" labels.

| | |
|--------------|--|
| Post, Parcel | Forbidden |
| Sea | Class 4.3 (3) (IMDG) |
| Road, Rail | Class 4.3 (3) (DOT, RID/ADR) |
| Air | Class 4.3 (3) (IATA) |
| | 1.0 L maximum per inner glass container. |
| | 1.0 L maximum per outer container. |
| | Cargo aircraft only |

For shipments within Europe, labeling for supply requirements are:

| | |
|------------|--------------------------------|
| F | Flammable |
| C | Corrosive |
| R&S Phrase | See Material Safety Data Sheet |

Responsible Care® initiative dictates that all shipments must be transported in a DOT-approved vehicle in a responsible manner (i.e., no flat bed trucks).

Additional Resources

Refer to the Organometallics and Reactive Specialty Organics Safe Handling Guide available on-line at www.fmclithium.com.