

## Lectro<sup>®</sup> Max400

**Chemical Name** Lithium Ingot, Electrochemical Grade

**Formula** Li

**Appearance** Metallic silver in color

**Application** Anode material for lithium batteries

<b>Product Specifications</b>	Li	99.90 wt% min
	Na	100 wppm max
	Ca	150 wppm max
	K	100 wppm max
	Fe	20 wppm max
	Si	100 wppm max
	Cl	60 wppm max
	N	300 wppm max

Standard size: 6" diameter x 20" length. Custom sizes available.

<b>Physical Properties</b>	Formula weight	6.94
	True density	0.534 g/cm <sup>3</sup>
	Melting point	180.5°C

**Toxicity/Safety Data** Flammable solid. Water reactive. Reacts violently with water to give off corrosive dust and flammable hydrogen gas. Elevated temperatures, above melting point (180.5°C/357°F), can result in spontaneous ignition in humid air. Corrosive to eyes (may cause blindness), skin, nose, throat and stomach.

*COMPLETE INFORMATION ON TOXICITY AND SAFETY IS CONTAINED IN THE FMC MATERIAL SAFETY DATA SHEET (MSDS) AVAILABLE FOR THIS PRODUCT.*

**Handling/Storage/Disposal** Can be handled in open atmosphere at room temperature, either coated with mineral oil or where relative humidity is maintained below 50%. To maintain best quality, humidity levels of less than 2% are recommended. Wear safety glasses or goggles and dry rubber gloves. Store in original unopened shipping container. Once opened, store in argon atmosphere or mineral oil. Keep away from water, humid air, acids and oxidizing materials. Keep away from heat, sparks and flame.

### Air Treatment Construction Energy Fine Chemicals Glass & Ceramics Greases & Lubricants Polymers Pool Water Treatment

MARKETS SERVED	<b>NORTH AMERICA AND HEADQUARTERS</b> FMC Lithium Seven LakePointe Plaza 2801 Yorkmont Road, Suite 300 Charlotte, NC 28208 P: +1.704.426.5300 F: +1.704.426.5370	<b>EUROPE</b> FMC Chemicals Commercial Road Bromborough Merseyside CH62 3NL, England P: +44.151.482.7356 F: +44.151.482.7361	<b>JAPAN</b> FMC Lithium 9F, Aoyama Building 1-2-3, Kita-Aoyama Minato-ku, Tokyo 107-0061, Japan T: +81.3.3402.3716 F: +81.3.3402.3700	<b>CHINA</b> FMC Lithium 15F Far East International Plaza No. 317 Xianxia Road Shanghai 200051 P. R. China T: +86.21.6235.1919 T: +86.21.6235.1917	<b>INDIA</b> FMC India Private Limited Embassy Star 8, Palace Road High Grounds Bangalore 560052, India T: +91.80.2238.4311 F: +91.80.2238.5255	<b>TAIWAN</b> FMC Lithium 9F-1, 263 Tun Hwa S. Rd. Sec. 1 Taipei, Taiwan T: +866.2.2705.4400 T: +866.2.2702.7460
----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

## LECTRO® MAX 400 ANODE MATERIAL

CAS No. 7439-93-2

FMC Product Code No. 452

**Shipping Containers** Lectro Max 400 is individually dry packed under argon in hermetically sealed aluminized polyester pouches, overpacked in a steel drum.

**Shipping Limitations** Shipments of lithium metal are described as "Lithium, UN 1415," PG I. All shipments are Hazard Class 4.3 and require "Dangerous When Wet" labels.

Post, Parcel	Not acceptable	
Sea	Class 4.3	(IMDG)
Road, Rail	Class 4.3.11 a	(RID/ADR)
Air	15kg max.	Cargo aircraft only

For shipments within Europe labeling for supply requirements are:

F	Highly Flammable
C	Corrosive
R&S phrases	See Material Safety Data Sheet (MSDS)

Responsible Care initiative dictates that all shipments of lithium chemicals must be transported in an approved vehicle in a responsible manner (i.e., no flat bed trucks).

**Lectro Battery Products** FMC provides a comprehensive line of products for battery applications including additional Lectro Max Anode Materials, Lectro Lyte Salts, and lithium precursors for producing critical battery materials. FMC possesses extensive capabilities to develop and customize products and packaging to meet specific customer requirements. FMC is ISO 9001:2000 certified.

For more information on these products, please call, or visit our website at [www.fmclithium.com](http://www.fmclithium.com). Let FMC Lithium fulfill your battery material needs.