

LectroLyte⁺700

Chemical Name Lithium Fluoride, Electrochemical Grade

Formula LiF

Appearance White powder

Application Electrolyte salt for lithium batteries

Product Specifications	LiF	98.5 wt% min
	H ₂ O*	0.50 wt% max
	Alkalinity (as LiOH)	0.5 wt% max
	Acidity (as HF)	200 wppm max
	Fe ₂ O ₃	500 wppm max
	SO ₄	1800 wppm max

* Value (as weight loss) determined by drying at 110°C for 2 hours.

Physical Properties	Formula weight	25.94
	True density @ 20°C	2.64 g/cm ³
	Melting point	848°C

Toxicity/Safety Data Odorless, white powder. This product may be irritating to the eyes, skin and mucous membranes.

COMPLETE INFORMATION ON TOXICITY AND SAFETY IS CONTAINED IN THE FMC MATERIAL SAFETY DATA SHEET (MSDS) AVAILABLE FOR THIS PRODUCT.

Handling/Storage/Disposal Avoid contact with eyes, skin or clothing. Use with adequate ventilation. Wear safety glasses or goggles and rubber gloves. Wash thoroughly after handling. Keep away from strong acids. Keep container closed.

Air Treatment Construction Energy Fine Chemicals Glass & Ceramics Greases & Lubricants Polymers Pool Water Treatment

MARKETS SERVED	NORTH AMERICA AND HEADQUARTERS FMC Lithium Seven LakePointe Plaza 2801 Yorkmont Road, Suite 300 Charlotte, NC 28208 P: +1.704.426.5300 F: +1.704.426.5370	EUROPE FMC Chemicals Commercial Road Bromborough Merseyside CH62 3NL, England P: +44.151.482.7356 F: +44.151.482.7361	JAPAN FMC Lithium 9F, Aoyama Building 1-2-3, Kita-Aoyama Minato-ku, Tokyo 107-0061, Japan T: +81.3.3402.3716 F: +81.3.3402.3700	CHINA FMC Lithium 15F Far East International Plaza No. 317 Xianxia Road Shanghai 200051 P. R. China T: +86.21.6235.1919 F: +86.21.6235.1917	INDIA FMC India Private Limited Embassy Star 8, Palace Road High Grounds Bangalore 560052, India T: +91.80.2238.4311 F: +91.80.2238.5255	TAIWAN FMC Lithium 9F-1, 263 Tun Hwa S. Rd. Sec. 1 Taipei, Taiwan T: +866.2.2705.4400 F: +866.2.2702.7460
----------------	--	---	---	--	--	--

Shipping Containers 110 lb. sealed in a 20-gallon fiber drum

Shipping Limitations Shipments of lithium fluoride are not classed as hazardous for transport. Shipments by post, parcel, air, water, rail, or road are acceptable within each carrier's weight limits and packaging requirements.

For shipments within Europe labeling for supply requirements are:

Xn	Harmful
R&S phrases	See Material Safety Data Sheet (MSDS)

Responsible Care[®] initiative dictates that all shipments of lithium chemicals must be transported in an approved vehicle in a responsible manner (i.e., no flat bed trucks).

Lectro Battery Products FMC provides a comprehensive line of products for battery applications including additional Lectro Lyte Salts, Lectro Max Anode Materials, and lithium precursors for producing critical battery materials. FMC possesses extensive capabilities to develop and customize products and packaging to meet specific customer requirements. FMC is ISO 9001:2000 certified.

For more information on these products, please call, or visit our website at www.fmclithium.com. Let FMC Lithium fulfill your battery material needs.