

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Lithium Magnesium Alloy
CHEMICAL FAMILY: Alkali Metal Magnesium Alloy
MOLECULAR FORMULA: Li and Mg
SYNONYM(s): Lithium Magnesium Alloy: ingot, rod, foil, precuts
ALTERNATE TRADE NAME(S): Lectro® Max 130 Anode Material
GENERAL USE: Industrial Manufacturing

MANUFACTURER
FMC CORPORATION
Lithium Division
P.O. Box 795
Bessemer City, NC 28016-0795
General Information: (704) 868-5300

Emergency Telephone Numbers:
CHEMTREC (800) 424-9300
Emergency Phone (704) 629-5361 (Plant) Call Collect 24 Hr/Day
Emergency Phone (303) 595-9048 (Medical) Call Collect

2. HAZARDS IDENTIFICATION

CLASSIFICATION: Substances and mixtures, which on contact with water, emit flammable gases; Category 1
Corrosive to skin; Category 1A

LABELING:

SYMBOLS: Flame , Corrosion
SIGNAL WORD: Danger
HAZARD STATEMENTS: In contact with water releases flammable gases, which may ignite spontaneously
Causes severe skin burns and eye damage

PRECAUTIONARY STATEMENTS:

Prevention:

Keep from any possible contact with water, because of violent reaction and possible flash fire.
Protect from moisture.
Handle under inert gas, or alternatively may be handled in open atmosphere at room temperature, either coated with mineral oil or where relative humidity is maintained below 50%. To maintain best quality, humidity levels of less than 2% are recommended.
Wear safety glasses or goggles for general use. Full flame-resistant face shield required if metal is in a molten state.
Wear dry rubber gloves for general use. Wear full flame-resistant clothing if the metal is handled or used in a molten state.
Do not breathe dusts or mists.
Wash thoroughly after handling.

Response

In case of fire DO NOT USE WATER, SAND OR CARBON DIOXIDE.
Use graphite, copper powder, Lith-X (Ansul). If not available, dry sodium chloride, dry (anhydrous) calcium oxide or dry lithium chloride can be used.

Wash contaminated clothing before reuse.

First Aid

See Section 4 of the MSDS.

Storage

See Section 7 of the MSDS.

Disposal

See Section 13 of the MSDS.

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS #</u>	<u>EC No.</u>	<u>Wt.%</u>	<u>Classification, Hazard Statement Codes</u>	
Lithium metal	7439-93-2	231-102-5	70-95	Water-react. Cat. 1	H260
				Skin Corr. Cat 1A	H314
Magnesium metal	7439-95-4	231-104-6	5-30	Flam. Sol. Cat 1	H228
				Water-react. Cat 2	H261
				Self-heat. Cat 1	H252

4. FIRST AID MEASURES

EYES:

Immediately flush with water for at least 15 minutes, lifting the upper and lower eyelids intermittently. See a medical doctor or ophthalmologist immediately.

SKIN:

Quickly wipe off as much as possible, then immediately flush with plenty of water while removing contaminated clothing and/or shoes. Thoroughly wash with soap and water. Obtain immediate medical attention. Contact a medical doctor if necessary.

INGESTION:

Quickly wipe material from the mouth and rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. See a medical doctor immediately.

INHALATION:

Remove to fresh air. If breathing difficulty or discomfort occurs and persists, see a medical doctor. If breathing has stopped, give artificial respiration and see a medical doctor immediately.

NOTES TO MEDICAL DOCTOR:

This product is corrosive and reacts violently with water. Treatment should first remove as much of the material as possible as quickly as possible, then flush with very large quantities of water. Ingestion presents a singular problem as emesis may produce esophageal damage and/or aspiration damage; dilution with water or other water-containing materials may produce a reaction that exacerbates the corrosive activity. Consideration may be given to gastric lavage with a large diameter tube for removal of material and then dilution with large amounts of water.

Esophagoscopy may be of assistance in this procedure and to assess extent of damage. Treatment is otherwise symptomatic and supportive.

5. FIRE FIGHTING MEASURES

FLAMMABLE LIMITS:

Upper: Not available Lower: Not available.

GENERAL HAZARD:

Flammable solid. Water reactive.

EXTINGUISHING MEDIA:

DO NOT USE WATER, SAND OR CARBON DIOXIDE. Use graphite, copper powder, Lith-X (Ansul). If not available, dry sodium chloride, dry (anhydrous) calcium oxide or dry lithium chloride can be used.

HAZARDOUS COMBUSTION PRODUCTS:

Lithium oxide, lithium hydroxide, magnesium hydroxide

FIRE FIGHTING PROCEDURES:

Wear full protective clothing and self-contained breathing apparatus (SCBA) approved for fire fighting. This is necessary to protect against the hazards of heat, products of combustion and oxygen deficiency. Do not breathe smoke, gases or vapors generated.

Lithium fires can throw off molten lithium metal particles. Burning lithium releases corrosive lithium oxide dust and fumes. Lithium

metal can reignite after fire is initially extinguished. Never leave extinguished fire unattended. After all material has apparently burned and cooled, carefully turn over remaining residue and be prepared to reextinguish should reaction occur. Carefully place residue in steel drum, using a long-handled shovel, and cover with extinguishing media.

For additional fire fighting information, see National Fire Protection Assn. Standard NFPA 485.

179°C (lithium metal)

Water reactivity and flammability of solid.

AUTOIGNITION TEMPERATURE:
PROPERTIES CONTRIBUTING TO

FLAMMABILITY:

FLASH POINT:

SENSITIVITY TO STATIC DISCHARGE:

SENSITIVITY TO IMPACT:

Not applicable

Not applicable

Not applicable

COMMENTS:

(See Section 10, Stability and Reactivity)

6. ACCIDENTAL RELEASE MEASURES

RELEASE NOTES:

Remove all sources of ignition. To prevent ignition, cover with mineral oil (or kerosene), soaking thoroughly, and place in oiled steel drums which are approved for transport. Keep water and moisture away from spilled material. Dispose of waste according to local and Federal laws and regulations.

Before cleanup measures begin, review the entire MSDS with particular attention to Section 3, Emergency Overview and Potential Health Effects; and Section 8, Recommended Personal Protective Equipment.

7. HANDLING AND STORAGE

HANDLING:

Can be handled in open atmosphere at room temperature, either coated with mineral oil or where relative humidity is maintained below 50%. To maintain best quality, humidity levels of less than 2% are recommended. Wear safety glasses or goggles and dry rubber gloves.

STORAGE:

Store in original unopened shipping container. Once opened, store in argon atmosphere or mineral oil. Keep away from water, humid air, acids and oxidizing materials. Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Chemical Name

**TWA
(ACGIH)**

**STEL/Ceiling
(ACGIH)**

**PEL
(OSHA)**

**STEL/Ceiling
(OSHA)**

None

ENGINEERING CONTROLS:

Use local exhaust ventilation to keep airborne concentrations below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

<u>Eyes And Face:</u>	Safety glasses or goggles for general use. Full flame-resistant face shield required if metal is in a molten state.
<u>Respiratory:</u>	None
<u>Protective Clothing:</u>	Dry rubber gloves for general use. Wear a full flame-resistant face shield if the metal is handled or used in a molten state.
<u>Work Hygienic Practices:</u>	Quick-drench eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>ODOR:</u>	Odorless
<u>APPEARANCE:</u>	Silvery-white soft metal solid
<u>pH:</u>	(1% solution) @ 25°C: >12
<u>PERCENT VOLATILE:</u>	Not applicable
<u>VAPOR PRESSURE:</u>	Not applicable
<u>VAPOR DENSITY:</u>	Not applicable
<u>BOILING POINT:</u>	1317°C (2400°F) (Li metal with 1% Na)
<u>MELTING POINT:</u>	180.5°C (357°F) (Li metal with 1% Na)
<u>SOLUBILITY IN WATER:</u>	Reacts violently with water
<u>EVAPORATION RATE(Butyl Acetate = 1):</u>	Not applicable
<u>SPECIFIC GRAVITY:</u>	0.61 g/cc, 0.5 g/cc (Li)
<u>MOLECULAR WEIGHT:</u>	6.94 (Li), 24.31 (Mg)
<u>COEFF. OIL/WATER:</u>	Not applicable
<u>ODOR THRESHOLD:</u>	Not applicable
<u>FLAMMABLE LIMITS:</u>	Upper: Not available Lower: Not available.
<u>FLASH POINT:</u>	Not applicable
<u>AUTOIGNITION TEMPERATURE:</u>	179°C (Li metal)
<u>VISCOSITY:</u>	Not applicable
<u>FLAMMABILITY:</u>	Reacts with water to produce hydrogen, a flammable gas.
<u>DECOMPOSITION TEMPERATURE:</u>	Not available
<u>EXPLOSIVE PROPERTIES:</u>	Not explosive
<u>OXIDIZING PROPERTIES:</u>	Not an oxidizer

10. STABILITY AND REACTIVITY

<u>CONDITIONS TO AVOID:</u>	Temperatures above the melting point, and contact with water, moisture or humid air.
<u>STABILITY:</u>	Stable
<u>POLYMERIZATION:</u>	Will not occur
<u>HAZARDOUS DECOMPOSITION PRODUCTS:</u>	Lithium and magnesium are elements and do not decompose. However, lithium is highly reactive in contact with many other substances, releasing large quantities of heat and/or hazardous products. It can react violently with water, the humidity in air, and the moisture in other substances, releasing hydrogen gas, which may catch fire explosively. Corrosive fumes of lithium oxide and/or lithium hydroxide are also released.
<u>INCOMPATIBLE MATERIALS:</u>	Acids, oxidizers, oxygen, nitrogen, or carbon dioxide

11. TOXICOLOGICAL INFORMATION

<u>Eye Contact:</u>	No data available for the product. Corrosive.
<u>Skin Contact:</u>	No data available for the product. Corrosive.

Skin Absorption: No data available for the product.
Corrosive.

Ingestion: No data available for the product.
Corrosive.

Inhalation: No data available for the product.
Corrosive.

Acute Effects From Overexposure:

This product is extremely reactive with body moisture and is corrosive to skin, nose, throat, stomach and eyes (may cause blindness).

Chronic Effects From Overexposure:

No data available for the product.

Sensitization: No

Carcinogenicity: EH40: Not listed.
IARC: Not listed.
NTP: Not listed.
OSHA: Not considered a carcinogen under OSHA.
ACGIH: Not listed

Mutagenicity: No

Reproductive Toxicity: No

12. ECOLOGICAL INFORMATION

Ecotoxicological Information:

No data available for the product.

Chemical Fate Information:

Lithium metal reacts violently with water. The hydrolysis products consist of hydrogen gas and lithium hydroxide. The hydroxide ion may affect the pH of the water.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of waste according to local and Federal laws and regulations.

14. TRANSPORT INFORMATION

UN NUMBER: UN3208

PROPER SHIPPING NAME: Metallic substance, water reactive, N.O.S (lithium magnesium alloy)

CLASSIFICATION: 4.3, Dangerous when wet

LABELS: Dangerous when wet

PACKING GROUP: I

FLASH POINT: Not applicable

CUSTOM TARIFF NO: 2805.19.9000

MARINE POLLUTANT: No

PIH: Not designated Poison Inhalation Hazard by US DOT.

15. REGULATORY INFORMATION

UNITED STATES

SECTION 311 HAZARD CATEGORY (40 CFR 370):
SECTION 313 REPORTABLE INGREDIENTS (40 CFR 372):

Reactive, fire hazard, immediate (acute) health hazard.
This product does not contain a toxic chemical subject to the reporting requirements of Section 313 of Emergency Planning and Community Right-To-Know Act of 1986.

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
CERCLA HAZARDOUS SUBSTANCE (40 CFR 302.4):

Not listed

TSCA SEC 12B EXPORT NOTIFICATION:

Not listed
This product is not subject to TSCA 12 (b) Export Notification Requirements.

TSCA INVENTORY STATUS (40 CFR 710):

Listed

CANADA
WHMIS:

Product Identification No.: 3208
Hazard Classification: Class B, Div. 6 (Reactive Flammable Materials)
Class E (Corrosive)
Ingredient Disclosure List: Not listed

16. OTHER INFORMATION

REVISION SUMMARY: Revision # 3: Regular review completed. Sections 2, 3, 9, 14 & 16 revised.

NFPA RATING

HEALTH: 3
FLAMMABILITY: 3
REACTIVITY: 2
SPECIAL: ~~W~~

This MSDS has been prepared to meet U. S. OSHA Hazard Communication Standard, 29 CFR 1910.1200 and Canada's Workplace Hazardous Materials Information System (WHMIS) requirements.
type 5a

Copyright 2009. FMC Corporation, Lithium Division. All Rights Reserved. FMC Lithium, the FMC Lithium logo and Lectro® are trademarks of FMC Corporation.